

## Harvi-Foil® Single Sided

### Application

Harvi-Foil® Single Sided is a single sided reflective foil laminate.


It is only recommended for use as laminate facing for bulk insulation material such as glass wool.

Harvi-Foil® products should not be used where fire retardant properties are required.

### Features and Benefits

- Single sided to provide a low cost solution for secondary lamination to bulk insulation
- Two-way fibreglass reinforcement for strength and edge tear resistance
- Highly reflective to enhance lighting conditions
- Low emissivity to limit heat loss
- Manufactured with pure aluminium foil to provide an effective barrier against vapour

### Technical Data



Physical Property Classifications in Accordance with AS/NZS4200.1			
Characteristics	Results	Characteristics	Results
Duty Classification	N/C	Resistance to Dry Delamination:	Pass
Tensile Strength (kN/m):	M.D.: ≥6.0      C.D.: N/C	Resistance to Wet Delamination:	Pass
Edge Tear Resistance:	M.D.: ≥65      C.D.: ≥65	Folding Endurance:	Pass
Emittance (Al Face):	Single Sided Reflective (≤0.05)	Water Barrier:	High
Vapour Barrier:	N/C	Flammability Index:	Unclassified
Shrinkage:	Pass		

The physical properties of Harvi-Foil® Single Sided have been tested by independent accredited laboratories. The nominal results are typically representative of performance. Test reports are available on request.

N/C = Not classified

## Green Star Compliant

*Fletcher Insulation* is committed to providing environmentally sustainable products. *Fletcher Insulation* products have Zero Ozone Depleting Potential in both manufacture and composition, complying with the GreenStar Insulant ODP Emissions credit requirement. Air quality during manufacture is maintained with total Volatile Organic Compound (VOC) emissions below quantifiable levels.

---

## Thermal Performance

When used in conjunction with an airspace, Harvi-Foil® Single Sided is an effective thermal insulation material due to the high reflectivity and low emissivity of its aluminium foil surfaces. The contribution of this product to Total R-value depends on installation and environmental conditions which include the effect of dust.

Comprehensive calculations of Total R-values for typical roof systems are illustrated in the ICANZ Insulation Handbook which can be found at [www.icanz.org.au](http://www.icanz.org.au)>PublicationsandReports>InsulationHandbook or contact Fletcher Insulation Export Office.

---

## Installation

Harvi-Foil® Single Sided should be installed in accordance with AS/NZS4200.2 Pliable Building Membranes and Underlays: Installation Requirements. Install with a 150mm overlap between runs, with each higher run lapping over the layer below. The product must be installed in such a way to prevent water from pooling.

Install external cladding without delay. To be effective as a thermal insulator there must be a minimum air gap of 40mm adjacent to at least one reflective foil face. Installing Harvi-Foil® Single Sided under battens is an effective method to achieve the required air space.

Aluminium foil is susceptible to alkali attack and therefore should not come in contact with wet concrete.

Where flame retardant properties are considered important please consult with your local supplier for the correct Sisalation® product to be used in your application.

### When specifying, state the following:

Product Name: Harvi-Foil® Single Sided

---

## Standard Roll Size

1.35m x 60m (81m<sup>2</sup>)

---

Note: Fletcher Insulation Pty Ltd reserves the right to change product specifications without prior notification. Information in this publication and otherwise supplied to users as to the subject product is based on our general experience and is given in good faith, but because of the many factors which are outside our knowledge and control and affect the use of products, no warranty is given or is to be implied with respect to either such information or the product itself, in particular the suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application.

**Manufactured in Australia by Fletcher Insulation Pty Ltd. under an ISO9001 Certified Quality Management System**

Fletcher Insulation Pty Ltd. A Fletcher Building Company. ABN 72 001 175 355  
600 Woodstock Avenue, Locked Bag 19, Rooty Hill, NSW 2766, Australia. Phone: +649 579 6789 Fax: +649 567 5130  
[www.sisalation.com.au](http://www.sisalation.com.au) [www.insulation.com.au](http://www.insulation.com.au) [info@tasmaninsulation.com](mailto:info@tasmaninsulation.com)  
Rev A Oct 09



SINGLE SIDED

HARVI-FOIL®